




- •Accurate testing of vibration on the workshop machines.
- •For quick checking of unbalance misalignment, bearings and gears
- •Guard against mechanical malfunction
- •Holding tested value for 40 seconds
- •Automatic switch off after 40 seconds



Technical specifications

Model	TV200	TV260
Parameter	RMS of vibration velocity (mm/s)	Acceleration, Velocity, Displacement
Testing range	Velocity: 0.1mm/s ~ 199.9mm/s	Acceleration:0.01m/S ² ~199.9m/S ² (peak) Velocity: 0.01mm/s -199.9 mm/s(RMS) Displacement: 0.001mm -1.999 mm
Frequency range	Velocity:10Hz ~ 1kHz	(peak-peak) Acceleration: 10Hz ~ 1kHz Velocity: 10Hz ~ 1kHz Displacement: 10Hz ~ 500Hz
Accuracy	±5%±2	±5%±2
Display	$3^{1}/_{2}$ digits LCD refresh interval about 0.5 second	$3^{1}/_{2}$ digits LCD
Power supply	two button batteries(LR44 or SR44)	two button batteries(LR44 or SR44)
Battery capacity	Approx. 5 hours working continuously	Approx. 4.5 hours working continuously
Operating Temperature	0 ~ 40	0 ~ 40
Environment humidity	<85%	<85%
Dimension	150mm×22mm × 18mm	150mm × 22mm × 18mm
Dimension Weight	55g (include two batteries)	55g(include two batteries)

Standard delivery	7
-------------------	---

Main unit	1
Protective sheath	1
Button battery	2
TIME certificate	1
Instruction manual	1

• Warranty card

Optional accessories

None